

附表三、LTE-M1 終端設備頻譜波罩之頻道頻寬測試參數

頻道頻寬	下行結構	上行結構			
	頻譜波罩測試不適用	調變方式	資源區塊分配		
			FDD 及 HD-FDD	TDD	窄頻索引(註一)
低頻道、中頻道					
1.4MHz		QPSK	2	2	0
1.4MHz		QPSK	5	5	0
1.4MHz		QPSK	6	6	0
1.4MHz		16QAM	2	2	0
1.4MHz		16QAM	5	5	0
3MHz		QPSK	2	2	0
3MHz		QPSK	5	5	0
3MHz		QPSK	6	6	0
3MHz		16QAM	2	2	0
3MHz		16QAM	5	5	0
5MHz		QPSK	6	6	0
5MHz (註三)		16QAM	1	1	0
5MHz		16QAM	3	3	0
5MHz		16QAM	5	5	0
10MHz (註三)		QPSK	4	4	0
10MHz		QPSK	6	6	0
10MHz (註三)		16QAM	3	3	0
10MHz		16QAM	5	5	0
15MHz		QPSK	6	6	0
15MHz		16QAM	5	5	0
高頻道					
1.4MHz		QPSK	2	2	0
1.4MHz		QPSK	5	5	0
1.4MHz		QPSK	6	6	0
1.4MHz		16QAM	2	2	0
1.4MHz		16QAM	5	5	0
3MHz		QPSK	2	2	1
3MHz		QPSK	5	5	1
3MHz		QPSK	6	6	1
3MHz		16QAM	2	2	1
3MHz		16QAM	5	5	1
5MHz		QPSK	6	6	3
5MHz (註三)		16QAM	1	1	3
5MHz		16QAM	3	3	3
5MHz		16QAM	5	5	3
10MHz (註三)		QPSK	4	4	7
10MHz		QPSK	6	6	7
10MHz (註三)		16QAM	3	3	7
10MHz		16QAM	5	5	7
15MHz		QPSK	6	6	11
15MHz		16QAM	5	5	11

註：

- 一、窄頻索引(Narrowband Index)定義依 3GPP TS 36.211, 5.2.4 規定。
- 二、RB offset 設定值及應檢項目之測試方法，依 3GPP TS 36.521-1 技術標準規定。
- 三、僅適用於 Power Class 3 之用戶設備。