

附錄二：

網路提示音

Tones	Frequency (Hz)	Interrupter (IPM)	Level (dBm0)	Cadence (sec)
Dial Tone	350 + 440		-13	Continuous
Ringing Tone	440 + 480	20	-19	1 sec ON, 2 sec OFF
Busy Tone	480 + 620	60	-24	0.5 sec ON, 0.5 sec OFF
Re-order Tone	480 + 620	120	-24	0.25 sec ON, 0.25 sec OFF
Ring Current	20			1 sec ON, 2 sec OFF
ROH Tone	480 or 1400 + 2060 + 2450 + 2600		≥ -3	
Call-Waiting Tone A	440 + 480		-13	One pulse OFF, of 1.5 sec duration
Call-Waiting Tone B	350 + 440		-13	0.25 sec ON, 0.25 sec OFF, 0.25 sec, ON and 5.25 sec OFF.
Warning Tone			-17	2 cycles,
Do	392			0.5 sec
Mi	494			0.5 sec
So	587			1.5 sec
Confirmation Tone	350 + 440		-13	0.1 sec ON, 0.1 sec OFF, 0.3 sec ON
Special Dial Tone	350 + 440		-13	Three bursts of 0.1 sec ON, 0.1 sec OFF, each; and then steady ON.