

附表15、FR1 頻譜波罩規範值(參考 3GPP TS 38.521-1 Table 6.5.2.2.5-1)

發射限值 (dBm) / 頻道頻寬																							
Δf_{OOB} (MHz)	5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz	40 MHz	50 MHz	60 MHz	80 MHz	90 MHz	100 MHz	解析頻寬										
± 0 -1	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT						1 % 的 頻道頻寬										
± 0 -1								-24 +TT	-24 +TT	-24 +TT	-24 +TT	-24 +TT	30 kHz (註1)										
± 1 -5	-10 +TT	-10 +TT	-10 +TT	-10 +TT	-10 +TT	-10 +TT	-10 +TT	-10 +TT	-10 +TT	-10 +TT	-10 +TT	-10 +TT	1 MHz (註2)										
± 5 -6	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT	-13 +TT											
± 6 -10	-25 +TT																						
± 10 -15		-25 +TT	-25 +TT																				
± 15 -20														-25 +TT									
± 20 -25				-25 +TT																			
± 25 -30					-25 +TT																		
± 30 -35						-25 +TT																	
± 35 -40																							
± 40 -45							-25 +TT																
± 45 -50								-25 +TT															
± 50 -55														-25 +TT									
± 55 -60									-25 +TT														
± 60 -65																							
± 65 -80										-25 +TT													
± 80 -85																							
± 85 -90											-25 +TT												
± 90 -95																							

± 95-100											
± 100-105											-25 +TT

註1:在解析頻寬30kHz 時，其 Δf_{OoB} 之量測範圍為0.015 MHz 至0.985 MHz

註2:在解析頻寬1MHz 時，各段量測範圍之量測頻率起止點皆向內縮 0.5MHz。

註3:量測頻率範圍應以頻道頻寬之頻譜波罩規範值，量測至本規範第2點規定各適用頻段之最高及最低頻率以外。

註4:測試誤差(Test Tolerance, TT)如附表16。