

附表15、廣域範圍基地臺之操作頻帶不必要發射限制值 (NR bands >3GHz, BS Type 1-C, BS Type 1-H)(參考 3GPP TS 38.141-1 Table 6.6.4.5.2-3及 Table C.1-1)

量測濾波器-3dB 頻率點之偏移頻率 Δf	量測濾波器中心頻率點之偏移頻率 f_{offset}	限制值(註2)	解析頻寬
$0 \text{ MHz} \leq \Delta f < 5 \text{ MHz}$	$0.05 \text{ MHz} \leq f_{\text{offset}} < 5.05 \text{ MHz}$	$-5.2\text{dBm} - \frac{7}{5} \cdot \left(\frac{f_{\text{offset}}}{\text{MHz}} - 0.05 \right) \text{dB}$	100 kHz
$5 \text{ MHz} \leq \Delta f < \min(10 \text{ MHz}, \Delta f_{\text{max}})$	$5.05 \text{ MHz} \leq f_{\text{offset}} < \min(10.05 \text{ MHz}, f_{\text{offset}_{\text{max}}})$	-12.2 dBm	100 kHz
$10 \text{ MHz} \leq \Delta f \leq \Delta f_{\text{max}}$	$10.5 \text{ MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$	-13 dBm (註1)	1MHz
註1：本限制值不適用於 $\Delta f_{\text{max}} < 10 \text{ MHz}$ 。 註2：限制值得依附表41放寬。			