

附表17、中程範圍基地臺之操作頻帶不必要發射限制值 (NR bands >3GHz, Type 1-C, BS Type 1-H) ( $31 \text{ dBm} < P_{\text{rated},x} \leq 38 \text{ dBm}$ ) (參考 3GPP TS 38.141-1 Table 6.6.4.5.4-3及 Table C.1-1)

量測濾波器-3dB 頻率點之偏移頻率 $\Delta f$	量測濾波器中心頻率點之偏移頻率 $f_{\_offset}$	限制值(註2)	解析頻寬
$0 \text{ MHz} \leq \Delta f < 5 \text{ MHz}$	$0.05 \text{ MHz} \leq f_{\_offset} < 5.05 \text{ MHz}$	$P_{rated,x} - 51.2dB - \frac{7}{5} \left( \frac{f_{offset}}{MHz} - 0.05 \right) dB$	100 kHz
$5 \text{ MHz} \leq \Delta f < \min(10 \text{ MHz}, \Delta f_{max})$	$5.05 \text{ MHz} \leq f_{\_offset} < \min(10.05 \text{ MHz}, f_{\_offset_{max}})$	$P_{rated,x} - 58.2dB$	
$10 \text{ MHz} \leq \Delta f \leq \Delta f_{max}$	$10.05 \text{ MHz} \leq f_{\_offset} < f_{\_offset_{max}}$	$\text{Min}(P_{rated,x} - 60dB, -25dBm)$ (註1)	
註1：本限制值不適用於 $\Delta f_{max} < 10 \text{ MHz}$ 。			
註2：限制值得依附表41放寬。			