

附表 59、WCDMA FDD 終端設備 Band 3 混附發射限制值

頻率範圍	解析頻寬	最大允許值
$462.5 \text{ MHz} \leq f \leq 467.5 \text{ MHz}$	1 MHz	-50 dBm
$703 \text{ MHz} \leq f \leq 803 \text{ MHz}$	1 MHz	-50 dBm
$791 \text{ MHz} \leq f \leq 821 \text{ MHz}$	3.84 MHz	-60 dBm
$852 \text{ MHz} \leq f \leq 859 \text{ MHz}$	1 MHz	-50 dBm
$859 \text{ MHz} \leq f \leq 894 \text{ MHz}$	3.84 MHz	-60 dBm (註)
$921 \text{ MHz} \leq f < 925 \text{ MHz}$	100 kHz	-60 dBm
$925 \text{ MHz} \leq f \leq 935 \text{ MHz}$	100 kHz	-67 dBm
	3.84 MHz	-60 dBm
$935 \text{ MHz} < f \leq 960 \text{ MHz}$	100 kHz	-79 dBm
	3.84 MHz	-60 dBm
$1447 \text{ MHz} \leq f \leq 1467 \text{ MHz}$	1 MHz	-50 dBm
$1452 \text{ MHz} \leq f \leq 1496 \text{ MHz}$	3.84 MHz	-60 dBm
$1475.9 \text{ MHz} \leq f \leq 1510.9 \text{ MHz}$	3.84 MHz	-60 dBm (註)
$1805 \text{ MHz} \leq f \leq 1880 \text{ MHz}$	3.84 MHz	-60 dBm
$1880 \text{ MHz} \leq f \leq 1920 \text{ MHz}$	3.84 MHz	-60 dBm
$1884.5 \text{ MHz} \leq f \leq 1915.7 \text{ MHz}$	300 kHz	-41 dBm (註)
$2010 \text{ MHz} < f < 2025 \text{ MHz}$	3.84 MHz	-60 dBm
$2110 \text{ MHz} \leq f \leq 2170 \text{ MHz}$	3.84 MHz	-60 dBm
$2170 \text{ MHz} \leq f \leq 2200 \text{ MHz}$	1 MHz	-50 dBm
$2300 \text{ MHz} \leq f \leq 2400 \text{ MHz}$	3.84 MHz	-60 dBm
$2496 \text{ MHz} \leq f \leq 2570 \text{ MHz}$	1 MHz	-50 dBm
$2570 \text{ MHz} \leq f \leq 2690 \text{ MHz}$	3.84 MHz	-60 dBm
$3510 \text{ MHz} \leq f \leq 3590 \text{ MHz}$	3.84 MHz	-60 dBm
$3400 \text{ MHz} \leq f \leq 3800 \text{ MHz}$	1 MHz	-50 dBm

註：僅適用於 1744.9 MHz 至 1784.9 MHz 內之傳輸。